

D Depth of Channel & Weight Per Ft.	Weight For 20'	WT Thickness Of Web in Inches	FW Width Of Flange in Inches
3" X 3.5 lbs.	70	0.14	1.36
3" X 4.1 lbs.	82	0.17	1.41
3" X 5.0 lbs.	100	0.258	1.498
3" X 6.0 lbs.	120	0.356	1.596
4" X 4.5 lbs.	90	0.145	1.52
4" X 5.4 lbs.	108	0.18	1.58
4" X 6.25 lbs.	125	0.247	1.647
4" X 7.25 lbs.	145	0.32	1.72
5" X 6.7 lbs.	134	0.19	1.75
5" X 9.0 lbs.	180	0.325	1.885
6" X 8.2 lbs.	164	0.2	1.92
6" X 10.5 lbs.	210	0.314	2.034
6" X 13.0 lbs.	260	0.437	2.157
7" X 9.8 lbs.	196	0.21	2.09
7" X 12.25 lbs.	245	0.314	2.194
7" X 14.75 lbs.	295	0.419	2.299
8" X 8.5 lbs.	170	0.18	1.875
8" X 11.5 lbs.	230	0.22	2.26
8" X 13.75 lbs.	275	0.303	2.343
8" X 18.75 lbs.	375	0.487	2.527
9" X 13.4 lbs.	268	0.23	2.43
9" X 15.0 lbs.	300	0.285	2.485
9" X 20.0 lbs.	400	0.448	2.648
10" X 15.3 lbs.	306	0.24	2.6
10" X 20.0 lbs.	400	0.379	2.739
10" X 25.0 lbs.	500	0.526	2.886
10" X 30.0 lbs.	600	0.673	3.033



D Depth of Channel & Weight Per Ft.	Weight For 20'	WT Thickness Of Web in Inches	FW Width Of Flange in Inches
12" X 20.7 lbs.	414	0.28	2.94
12" X 25.0 lbs.	500	0.387	3.047
12" X 30.0 lbs.	600	0.51	3.17
15" X 33.9 lbs.	678	0.4	3.4
15" X 40.0 lbs.	800	0.52	3.52
15" X 50.0 lbs.	1000	0.716	3.716